

	testo 865	testo 868	testo 871	testo 872	testo 875-2i	testo 882	testo 885	testo 890
<b>Artikelnr.</b>	0560 8650	0560 8681	0560 8712	0560 8721	0560 0875 V2	0560 0882	0563 0885 V2	0563 0890 V2
<b>Bild</b>								
<b>IR-upplösning</b>	160 x 120 pixlar	160 x 120 pixlar	240 x 180 pixlar	320 x 240 pixlar	160 x 120 pixlar	320 x 240 pixlar	320 x 240 pixlar	640 x 480 pixlar
<b>SuperResolution-upplösning</b>	320 x 240 pixlar	320 x 240 pixlar	480 x 360 pixlar	640 x 480 pixlar	320 x 240 pixlar	640 x 480 pixlar	640 x 480 pixlar	1280 x 960 pixlar
<b>NETD (värmekänslighet)</b>	120 mK	100 mK	90 mK	60 mK	< 50 mK bei +30 °C	< 50 mK bei +30 °C	< 30 mK bei +30 °C	< 40 mK bei +30 °C
<b>Synfält (FOV)</b>	31° x 23°	31° x 23°	35° x 26°	42° x 30°	32° x 23°	32° x 23°	30° x 23°	42° x 32°
<b>Synfält vidvinkeloptik (FOV)</b>	31° x 23°	31° x 23°	35° x 26°	42° x 30°	32° x 23°	32° x 23°	30° x 23°	42° x 32°
<b>Synfält teleobjektiv (FOV)</b>	-	-	-	-	9° x 7° (tillval)	-	11° x 9° (tillval)	15° x 11° (tillval)
<b>Synfält super-teleobjektiv (FOV)</b>	-	-	-	-	-	-	5° x 3,7° (tillval)	6,6° x 5° (Fast)
<b>Geometrisk upplösning (IFOV)</b>	3,4 mrad	3,4 mrad	2,6 mrad	1,3 mrad	3,3 mrad (Tele: 1,0 mrad)	1,7 mrad	1,7 mrad (Tele: 0,6 mrad)	1,13 mrad (Tele: 0,42 mrad)
<b>Fokus</b>	Fast fokus	Fast fokus	Fast fokus	Fast fokus	Manuell fokus	Motorfokus och autofokus	Autofokus och manuell fokus	Autofokus och manuell fokus
<b>Minsta fokusavstånd IR</b>	< 0,5 m	< 0,5 m	< 0,5 m	< 0,5 m	0,1 m (Tele: 0,5 m)	0,2 m	0,1 m (Tele: 0,5 m)	0,1 m (Tele: 0,5 m)
<b>Mätområde</b>	-20 ... +280 °C	-30 ... +100 °C 0 ... +650° C	-30 ... +100 °C 0 ... +650° C	-30 ... +100 °C 0 ... +650° C	-30 ... +100 °C0 ... +350 °C +350 ... +550 °C (Hög temp)	-20 ... +100 °C0 ... +350 °C +350 ... +550 °C (Hög temp)	-30...+100°C 0...+350°C 0 ... +650 °C +350 ... +1200°C (Hög temp)	-30 ... +100 °C 0 ... +350 °C 0 ... +650 °C +350 ... +1200°C (Hög temp)